



PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS  
 DRAWING IS THE SOLE PROPERTY OF  
 PRINCETEL, INC. ANY REPRODUCTION  
 IN PART OR AS A WHOLE WITHOUT THE  
 WRITTEN PERMISSION OF PRINCETEL,  
 INC. IS PROHIBITED.

STANDARD SPECIFICATIONS	
PARAMETERS	VALUES
Wavelength range	1270-1610 nm for SM; 850 and 1310 nm for MM
Insertion loss	<5 dB (typical: 2-3 dB)
Insertion loss ripple	~+/-0.5 to 1 dB
Return loss (SM)	>45 dB
Crosstalk	>50 dB (typical: 63 dB)
Maximum speed	400 rpm
Estimated life cycle	100-200 million revolutions
Working temperature	-20 to 65 C
Storage temperature	-25 to 75 C
Package style	Pigtails on both ends
Housing material	Stainless steel
Fiber types	Single or multimode
Jacket types	900um, 2mm, 3 mm (Kevlar/PVC or armor)
Connector types	ST, FC, LC, SC (PC and APC)
Vibration	MIL-STD-167-1A
Mechanical shock	MIL-STD-810G
IP rating	IP 60

UNLESS OTHERWISE SPECIFIED:			DATE		NAME	
DIMENSIONS ARE IN mm DO NOT SCALE DRAWING			DRAWN	10/26/2017	L. X.	PRINCETEL, INC.
TOLERANCES:			CHECKED	10/26/2017	R. Z.	
ANGULAR: ± 1/2°			ENG APPR.			
ONE PLACE DECIMAL ± 0.100			MFG APPR.			
TWO PLACE DECIMAL ± 0.050			Q.A.			
THREE PLACE DECIMAL ± 0.025			COMMENTS: FIRST ANGLE PROJECTION			TITLE:
MATERIAL:			ZJn, FORJ (n=2-4)			REV
			SIZE DWG. NO.			4
			B 2535-00-AD			PART NO.
			-			SHEET 1 OF 1